











## 翰达蝶阀型号编号原则

1	2	3	4	5	6	7	8	9	10
阀门特征	设计标准	连接方式	压力	驱动方式	阀体材料	阀杆材料	蝶板材料	密封圈材料	尺寸
DB标准	G - 国标 	8 - 对夹式 	150 LB	M 手动 	20-WCB	17 -17-4PH	20 -WCB	TT- PTFE	2"-120"
DF防火	A- 美标 	6 - 焊接 	300 LB	K 光杆 	34 -CF8	34 -CF8	34 -CF8	MT -RPTFT	DN50-DN3000
  防火结构和防火试验询价,LR,DNV,BV证书均可提供	J - 日标 	5 - 单法兰 	600 LB	G 涡轮 	36 -CF8M	36 -CF8M	36- CF8M	PL- PPL	例如： <b>DBA815W-P-201734-TT-24"</b> 即：标准美标对夹式高性能蝶阀，150磅，气动型，阀体：WCB，阀杆：17-4PH，蝶板：CF8,密封圈：PTFE,尺寸：24寸 对应图片如下  
	D - 德标 	4 - 双法兰 	900 LB	P 气动 	41 -CF3	13 -1CR13	41- CF3	PK -PEEK	
	B- 英标 	其他连接方式或定制焊接等形式欢迎询价咨询 其他国家标准，例如俄标等 请询价 info@handavalve.com	010- PN10	D 电动 	61 -CF3M	23 -2CR13	61 -CF3M	其他特殊材质例如 TFM1600, Inconel 625 等根据工况温度不同	
	其他国家标准，例如俄标等 请询价 info@handavalve.com		016- PN16	其他连接方式例如电液联动等驱动方式欢迎咨询	66 -蒙乃尔 88 -哈氏合金 其他特殊材料 例如双相钢	建议采用17-4PH,NICKEL -AL BR TRIM,monel K500	66- 蒙乃尔 88- 哈氏合金 同阀体材质		
			025- PN25						
			040 -PN40						
			100 -PN100						
			160 -PN160						
			10K -JIS						
			20K						
30K									
40K									